

TECHNICAL DATA SHEET

Mesh number thread n./cm	Weave	Mesh opening μm	Thread diameter μm	Open area %	Thickness μm	Ink volumen cm^3/m^2	Recommend ed tension Nw./cm.
10.260	1x1	740	260	55	480	246	42
21.145	1x1	340	140	50	250	125	42
24.120	1x1	300	120	51	210	105	42
34.100	1x1	210	100	45	165	70	35
43.80	1x1	150	80	41	130	55	35
48.70	1x1	135	70	41	115	46	32
55.64	1x1	115	64	39	102	40	30
62.64	1x1	90	64	32	106	35	32
71.55	1x1	80	55	30	90	30	28
77.55	1x1	70	55	25	88	24	28
90.48	1x1	55	48	25	78	20	33
100.40	1x1	58	40	32	65	21	27
110.40	1x1	48	40	27	65	17	30
120.34	1x1	45	34	30	55	16	27
140.30	1x1	35	30	26	48	13	25
140.34	1x1	30	34	20	55	10	30
150.30	1x1	37	30	30	45	14	29
150.34	1X1	33	34	24	58	14	38
165.27	1X1	33	27	30	40	12	24
165.30	1X1	30	30	25	45	11	26
180.27	1X1	28	27	26	43	11	25